









UNI HANGER / PANEL GRIPS










UNI HANGER / PANEL GRIPS

A		
		
UNI HANGER	PLUG (Ø 5 mm)	SCREW
7806.150	9.4931	9.4929

B1	B2	B3
		
TWISTER 1 mm STEELWIRE BLACK 150 cm	TWISTER 1 mm STEELWIRE BLACK 200 cm	TWISTER 1 mm STEELWIRE BLACK 300 cm
09.63150	09.63200	09.63300

C

PANEL GRIP BLACK (1-4 mm PANEEL)
7806.140

SIGN HANGING SYSTEMS



Artiteq has selected the Fischer UX 5x30 R plug to be used in combination with its hanging systems. The Fischer UX 5x30 R plug can be used in different kinds of materials, such as concrete, stone and plasterboard. Depending on the material, the plug can support a maximum load of 30 kg. The drill used with the plug must have a diameter of 5 mm. The plug is 30 mm in length. The screw used with the plug is 38 mm long and has a diameter of 3.5 mm (to be used in combination with a PZ2 bit).

To determine the maximum load of a signing hanging system, it must be known what type of mounting materials will be used and what surface (i.e. type of material) these will be attached to. The components of the signing hanging system all have a maximum bearing capacity. This is the maximum bearing capacity for the component itself and not the maximum bearing capacity that must be taken into account for the system as a whole. For the whole system, the load capacity that is recommended for the mounting material in combination with the respective base material, takes precedence.

For every signing hanging system, the weight that you wish to hang must be balanced against the maximum load capacity of the mounting material. If systems are hung from other hanging components, such as recessed ceilings, you have to know the maximum load of this hanging component before fitting our systems. The tables below show the maximum load capacity for the Fischer plug in combination with different materials and the maximum bearing capacity for each component for the different signing hanging systems.

TYPE	UX 5X 30		
RECOMMENDED LOADS IN THE RESPECTIVE BASE MATERIAL $F_{REC}^{2)}$			
Concrete	$\geq C20/25$	[kN]	0,30
Solid brick	$\geq Mz 12$	[kN]	0,20
Perforated sand-lime brick	$\geq KSL 12$	[kN]	0,30
Vertically perforated brick	$\geq Hlz 12$	[kN]	0,20
Aerated concrete	$\geq AAC 4$	[kN]	0,15
Gypsum plasterboard	12,5 mm	[kN]	0,10
Gypsum plasterboard	25 mm	[kN]	0,10
Gypsum fibreboard	(Fermacell)	[kN]	0,20
Gypsum block	$\rho \geq 0,9 \text{ kg/dm}^3$	[kN]	-

ART. NO.	DESCRIPTION	MAX. LOAD CAPACITY
7807.060	Suspension bracket Xpo Rail 1,2 mm	15 kg
7807.200	Steelwire + slider 1,2 mm 200 cm black	15 kg
7807.210	Steelwire + slider 1,2 mm 200 cm nickel	15 kg
7807.100	Ceiling Bracket black C01BL	15 kg
7807.110	Ceiling Bracket nickel C01NI	15 kg
7807.140	Ceiling Suspension auto grip 1,2 mm CS01NI	15 kg
7807.350	Steelwire 7x7 1,2 mm 10 m	15 kg
7805.052	Loop Hanger 1,0 mm - 1,5mm	10 kg
7807.120	Recessed Ceiling Clip 20 mm	5 kg
7807.130	Recessed Ceiling Clip 20 mm + suspension auto grip 1,2 mm	5 kg
7807.310	Steelwire + hook 1,2 mm 300 cm	15 kg
7807.010	Steelwire Hook auto grip 1,2 mm ST01BL	15 kg
7807.020	Steelwire Hook auto grip 1,2 mm ST01NI	15 kg
7807.030	Steelwire Hook auto grip 1,2 mm ST02NI	15 kg
7807.040	Steelwire Hook auto grip 1,2 mm ST03NI	15 kg
7807.400	Acoustic Spring 01-NI	5 kg
7807.050	Steelwire Clamphook auto grip 1,2 mm STC01NI	15 kg



1 Required safety factors are considered.
2 Valid for tensile load, shear load and oblique load under any angle